SAFETY DATA SHEET

Aqua Hyperfine, Blue

普羅森科技股份有限公司 2024-01-10 職安人員

SECTION 1 : IDENTIFICATION

1.1 Product identifier

Product name Aqua Hyperfine, Blue

Recommended use and restrictions on use

Recommended use For use in Phrozen 3D-printers

Restrictions on use Do not use in the situation that easily generate aerosol, steam.

1.2 Name, address and phone of manufacturer , importers or supplier

Manufacturer Phrozen Tech Co., Ltd.287 Niupu Rd, Xiangshan Dist, Hsinchu City 30091, TAIWAN(R.O.C)

Phone +886-3621-0505

Emergency phone / Fax +886-3621-0505 / +886-3539-6591

SECTION 2 : HAZARD IDENTIFICATION

2.1 Hazard classification

Skin corrosion/irritation Category 2 , Serious eye damage/eye irritation Category 1 ,
Skin sensitization Category 1
Specific target organ toxicity-repeated exposure Category 2
Hazardous to the aquatic environment (acute hazard) Category 1
Hazardous to the aquatic environment (chronic hazard) Category 3

2.2 Signal statement

Corrosion, Exclamation mark, Health hazard, Environment

2.3 Pictograms

2.4 Signal word Danger

2.5 Hazard statements

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause damage to organs through prolonged or repeated exposure
Very toxic to aquatic life with long lasting effects

2.6 Precautionary statements

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read carefully and follow all instructions.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, If present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Dispose of contents/container in accordance with local/regional/national/international regulations.

2.7 Other hazard

None

SECTION 3 : COMPOSITION / INFORMATION ON INGREDIENTS

3.1. Substances

Not relevant (mixture)

3.2. Mixtures

Components	CAS number	Weight %	Classification acc. to GHS
Oxybis(methyl-2,1-ethanediyl) diacrylate	57472-68-1	10 – 25%	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Eye Dam. 1 / H318
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3- epoxypropane, propane-1,2-diol acrylate and succinic anhydride	68958-77-0	10 – 25%	Skin Sens. 1 / H317 Acute Tox. 4 / H332 Aquatic Acute 1 / H400 Aquatic Chronic 4 / H413
(2,4,6-trioxo-1,3,5-triazine1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate	40220-08-4	10-25%	Eye Dam. 1 / H318 Skin Sens. 1 / H317 Aquatic Chronic 2 / H411
4-(1-oxo-2-propenyl)-morpholine	5117-12-4	10-25%	Acute Tox. 4 / H302

			STOT RE 2 / H373 Eye Dam. 1 / H318 Skin Sens. 1 /H317
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocy anatohexane	264888-31-5	10-25%	Acute Tox. 4 / H302 Skin Sens. 1B / H317 Aquatic Chronic 3 / H412
Additives1	Trade Secret	<2%	Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 4 / H413
Additives2	Trade Secret	<2%	Carc. 2 / H351

SECTION 4 : FIRST AID MEASURES

4.1. First-aid advice and recommendations for different routes of exposure

4.1.1 Inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Incase of respiratory tract irritation, consult a physician. Provide fresh air.

4.1.2 Skin Contact

Wash with plenty of soap and water.

4.1.3 Eyes Contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, freshwater for at least 10 minutes, holding the eyelids apart.

4.1.4 Ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2. Most important symptoms and hazardous effecects

None

4.3. Protection of First-aid personnel

None

4.4. Note for physician

None

SECTION 5 : FIRE-FIGHTING MEASURES

5.1 Applicable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

5.2 Specific hazards confronted during fire fighting

Carbon monoxide (CO), Carbon dioxide (CO2), Nitrogen oxides

5.3 Specific fire-fighting procedure

None

5.4 Specific protecttive equipments for fire-fighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precations

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2. Environmental precations

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3. Cleaning methods

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur(dia tomite), sand, universal binder. Covering of drains.

Place in appropriate containers for disposal. Ventilate affected area.

SECTION 7 : SAFETY HANDLING AND STORAGE

7.1. Handling

Use local and general ventilation. Use only in well-ventilated areas.

Do not eat, drink and smoke in work areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Wash hands after use.

Never keep food or drink in the vicinity of chemicals.

Never place chemicals in containers that are normally used for food or drink.

7.2. Storage

Storage at the area of cool,dry.

Keep away from heat ,direct sunlight, rainy and rapid temperature .

Storage temperature between 15°C/ 59°C to 35°C / 95°F.

Close the lid tightly when not in use.

SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Engineering controls

Provide adequate ventilation to the areas where the product is stored and/or handled.

8.2. Control Parameters

Component	TWA	STEL	CEILING	BEI s
Titanium dioxide	10 mg / m^3	15 mg /m^3	-	-

8.3. Personal protective equipment

8.3.1 Respiratory protection

In case of inadequate ventilation wear respiratory protection.

8.3.2 Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374.

For example : NBR: acrylonitrile-butadiene rubber

Material thickness : ⩾ 0.6mm

Breakthrough times of the glove material : > 480 minutes (permeation: level 6)

8.3.3 Eye protection

Use safety goggles.

8.3.4 Skin protection

Use clothing that provides complete protection to the skin.

8.4. Hygiene measures

Do not eat, drink and smoke in work areas.

Wash thoroughly after handling.

Keep clean of operation area.

Take off polluted clothing as soon as possible after work. The clothing can be re-wear only after washed in clean or discard.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Apperance and color	Blue viscous liquid	**Odor**	Typical acrylate
Odor threshold	N/A	**Melting point**	N/A
pH value	6-8	**Boiling point**	104.5 °C at 2.05 hPa
Flammable	N/A	**Flash point** **Testing method**	N/A N/A
Decomposition Temp	N/A		
Natural Temp	240℃	**Explosive limit**	N/A
Vapor pressure	0.5 hPa at 86.6 °C	**Vapor density**	N/A
Density	1.15 g /cm³ at 25 °C	**Solubility**	N/A
Octanol/water distribution coefficient (log Kow)	N/A	**Evaporaion rate**	N/A

SECTION 10: STABILITY AND REACTIVITY

10.1. Stability

Stable under normal condition.

10.2. Possible hazardous reation under specific conditions

None

10.3. Must avoid condition

UV-radiation/sunlight.

10.4. Must avoid substances

Oxidisers

10.5. Hazardous decomposted product

None

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Test data are not available for the complete mixture.

11.1. Exposure paths

None

11.2. Symptoms

None

11.3. Acute toxicity

Components	route	End point	Value
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3-epoxypropane, propane-1,2-diol acrylate and succinic anhydride	inhalation: vapour	LC50	11mg/l /4H
	inhalation: dust/mist	LD50	4.9mg/l/4H
4-(1-oxo-2-propenyl)-morpholine	Oral	LD50	> 588 mg/kg
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	Oral	LD50	>2000 mg/kg

11.4. Chronic toxicity

None

11.5. Reproductive and/or Developmental Effects

None

SECTION 12: ECOLOGICAL INFORMATION

The product has not been tested. The statement has been derived from the properties of the individual components.

12.1. Ecological toxicity

Aquatic toxicity (acute) of components of the mixture				
Components	**End point**	**Value**	**Species**	**Exposure time**
Oxybis(methyl-2,1-ethanediyl) diacrylate	LC50	4.64 mg/l	fish	96 h
	EC50	22.3 mg/l	aquatic invertebrates	48 h
	ErC50	16.7mg/l	algae	72h
	LL50	>100 mg/l	fish	96 h

4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3- epoxypropane, propane-1,2-diol acrylate and succinic anhyd ride	LC50	0.082mgl	fish	96h
	EC50	0.11mg/l	aquatic invertebrates	48h
	EL50	>100mg/l	aquatic invertebrates	48h
(2,4,6-trioxo-1,3,5-triazine1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate	LC50	9.43mg/l	fish	96h
	EC50	158.3mg/l	aquatic invertebrates	72h
	ErC50	25.7mg/l	algae	96h
4-(1-oxo-2-propenyl)-morpholine	LC50	>220mg/l	fish	72 h
	EC50	230mg/l	aquatic invertebrates	48 h
	ErC50	>120mg/l	algae	72h
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 1,6-diisocyanatohexane	EL50	58 mg/l	aquatic invertebrates	48 h
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	LC50	>90µg/l	fish	96 h
	EC50	>1175µg/l	aquatic invertebrates	48 h
	ErC50	>260µg/l	algae	72h

Aquatic toxicity (chronic) of components of the mixture

Components	End point	Value	Species	Exposure time
Oxybis(methyl-2,1-ethanediyl) diacrylate	EC50	>1,000 mg/l	microorganisms	30 min
4,4'-Isopropylidenediphenol, polymer with 1-chloro-2,3- epoxypropane, propane-1,2-diol acrylate and succinic anhydride	EC50	>1,000 mg/l	microorganisms	3h
phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	EC50	>100mg/l	microorganisms	3h

12.2. Per sistence and degradability

Degradability of components of the mixture

Components	Process	Degradation rate	Time	Source
Oxybis(methyl-2,1-ethanediyl) diacrylate	DOC removal	90–100 %	28d	ECHA
4,4'-Isopropylidenediphenol, polymer with	carbon dioxide	5%	29d	ECHA

1-chloro-2,3- epoxy propane, propane-1, 2-diol acrylate and s uccinic anhydride	generation			
(2,4,6-trioxo-1,3,5-tri azine1,3,5(2H,4H,6H) -triyl)tri-2,1-eth anediyl triacrylate	oxygen deple-tion	19.7%	28d	ECHA
2-Propenoic acid, 2-hy droxyethyl ester, polymer with 1,6-diis ocyanatohexane	carbon dioxide generation	5%	28d	ECHA
phenyl bis(2,4,6-trim ethylbenzoyl)-phosp hine oxide	carbon dioxide generation	1%	29 d	ECHA

12.3. Bio-accumulative potential

Components	BCF	Log kow	BOD/COD
Oxybis(methyl-2,1-et hanediyl) diacrylate		0.01- 0.39 (pHvalue : 7, 24°C)	
4,4'-Isopropylidenedi phenol, polymer with 1-chloro-2,3- epoxy propane, propane-1, 2-diol acrylate and s uccinic anhydride		1.1 (20.6°C)	
(2,4,6-trioxo-1,3,5-tri azine1,3,5(2H,4H,6H) -triyl)tri-2,1-eth anediyl triacrylate		1.09(pHvalue : 6.8, 25°C	
4-(1-oxo-2-propeny l)-morpholine		-0.46(21°C)	
2-Propenoic acid, 2-hydroxyethyl ester, p olymer with 1,6-diiso cyanatohexane		>2.8-<4.9(25°C)	
phenyl bis(2,4,6-trim ethylbenzoyl)-phosp hine oxide	<5	5.8(pHvalue : 8.3, 22°C)	

12.4. Mobility in soil

None

12.5. Other adverse effects

None

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste disposal methods

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

13.2. Sewage disposal method

Do not empty into drains. Avoid release to the environment.

13.3. Contaminated Packaging disposal method

Handle contaminated packages in the same way as the substance itself.

SECTION 14: TRANSPORT INFORMATION

Land transport USDOT	Not classified as dangerous goods under transport regulations.
Sea transport IMDG	Not classified as dangerous goods under transport regulations.
Air transport IATA/ICAO	Not classified as dangerous goods under transport regulations.
Further information	N/A
Other requirements	N/A

SECTION 15: REGULATORY INFORMATION

15.1. List of substances subject to authorisation (REACH, Annex XIV) / SVHC- candidate list

None of the ingredients are listed

15.2. Directive on the restriction of the use of certain hazardous substances in electrical

and electronic equipment (RoHS)

None of the ingredients are listed

15.3. Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

None of the ingredients are listed

15.4. Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

15.5. National inventories

Country	Inventory	Status
AU	AU AICS	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
DSL	Domestic Substances List (DSL)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
EU	EC Substance Inventory (EINECS, ELINCS, NLP)
EU	REACH registered substances
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
NZIoC	New Zealand Inventory of Chemicals
CICR	Chemical Inventory and Control Regulation
TCSI	Taiwan Chemical Substance Inventory

TSCA	Toxic Substance Control Act

SECTION 16: OTHER INFORMATION

Reference	US OSHA HCS 29 CFR 1910.1200 ,ECHA
Table formulation unit	Name : Phrozen Tech. Co. Ltd
	Address / Phone : 287 Niupu Rd, Xiangshan Dist, Hsinchu City 30091, TAIWAN(R.O.C) /+ 886-3-6210505
Table formulator	Job title : Occupational Safety & Health manager Name : Chun-Yao, Kuo
Table formulation Date	2024.01.10
Remarks	In the above described information, the symbol “N/A” means no relevant information currently.

To the best of our knowledge the information contained herein is accurate. However, Phrozen Tech. Co. Ltd. makes no warranty, expressed or implied, regarding the accuracy of these results to be obtained from the use thereof. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Phrozen Tech. Co. Ltd. assumes no responsibility for injury from the use of the product described herein.

END OF SAFETY DATASHEET